



Lineární plastový žlab ke stěně s bočním odtokem D40 Black

průtok ≈ 30-38 l/min | **min. stavební výška:** 50 mm | **průměr odtoku:** 40 mm

Moderní styl sprchového koutu se často vyznačuje jednoduchostí a funkcí prvků. Ozdobou Vaší koupelny může být naše široká nabídka odtokových žlabů s nerezovou mřížkou. Černé provedení mřížky nabízíme v šesti variantách.

Nerezové mřížky jsou velmi pečlivě zpracované a pevné. Vyrobeno z nerezové oceli dle DIN 1.4301 AISI 304.



ROZMĚRY ŽLABU

L	350 mm	450 mm	650 mm	750 mm	850 mm	950 mm
L1	415 mm	515 mm	715 mm	815 mm	915 mm	1015 mm
L2	295 mm	295 mm	595 mm	695 mm	795 mm	895 mm
Hmotnost [1 ks]	1,25 kg	1,43 kg	1,96 kg	2,12 kg	2,36 kg	2,70 kg

VLASTNOSTI ŽLABU


- určeno pro interiéry
- nízká stavební výška 50 mm
- výškové nastavení žlabu od 65 do 87 mm
- průtok lineárního žlabu 30-38 l/min. dle normy EN 1253
- kombinované řešení sifonu vodní hladina + uzavírací klapky
- zatížení lineárního žlabu K3 (300 kg)
- černá nerez mřížka 1,5 mm pouze v provedení mat
- rozměrová řada 350, 450, 550, 650, 750, 850, 950 mm
- snadná demontáž při čištění sifonu
- výška rámečku žlabu 15 mm
- varianta s mřížkou pro vložení dlažby
- zesílení těla žlabu žebrovaním
- sítko pro zachytávání nečistot

NÁHRADNÍ DÍLY

	obj. číslo
Klíč k vyjmutí mřížky – plastový	CH 439
Víko sifonu k linear. žlabu černé	CH 430 C
Těsnění pro víko sifonu	CH 431
Klapka k linear. žlabu černá	CH 432 C
Stavitelná podpora žlabu 47 mm	CH 433
Podstavec mřížky černý M,D,S,H,L	CH 463/1 C
Podstavec mřížky černý K/F	CH 462/1 C
Sítka žlabu D40 černé	CH 468 C
Samolepící hydroizolační fólie 1000×80 mm	391/7



NÁVOD
na instalaci





Linear floor drain for the wall with side outlet D40 Black



flow rate ~ 30-38 l/min | **lowest installation height:** 50 mm | **outlet diameter:** 40 mm

Modern shower design is often defined by simplicity and functionality. An elegant highlight of your bathroom can be our wide range of drain channels with stainless steel grates. We offer the black grate design in six variants.

The stainless steel grates are precisely crafted and highly durable. Made of stainless steel according to DIN 1.4301 AISI 304.



DRAIN DIMENSIONS

L	350 mm	450 mm	650 mm	750 mm	850 mm	950 mm
L1	415 mm	515 mm	715 mm	815 mm	915 mm	1015 mm
L2	295 mm	295 mm	595 mm	695 mm	795 mm	895 mm
Weight [1 pc]	1,25 kg	1,43 kg	1,96 kg	2,12 kg	2,36 kg	2,70 kg

FEATURES OF THE DRAIN

- designed for interior
- low installation height 50 mm
- drain height adjustment from 65 to 87 mm
- linear drain flow rate 30-38 l/min according to EN 1253
- combined siphon system with water seal and shut-off flaps
- load class K3 (300 kg)
- black stainless steel grate 1.5 mm only in matt finish
- available sizes 350, 450, 550, 650, 750, 850, 950 mm
- easy disassembly for siphon cleaning
- frame height 15 mm
- version with tile insert grate
- drain body reinforced with ribbing
- dirt strainer

SPARE PARTS

	order no.
Key for removing the grate – plastic	CH 439
Siphon cover for linear drain – black	CH 430 C
Siphon cover seal	CH 431
Flap for linear drain – black	CH 432 C
Height-adjustable support legs 47 mm	CH 433
Grate base black M,D,S,H,L	CH 463/1 C
Grate base black K/F	CH 462/1 C
Drain strainer D40 black	CH 468 C
Self-adhesive waterproofing membrane 1000×80 mm	391/7



INSTRUCTIONS
for installation

